The Flagpole Company PO Box 765 221 N. Main St. Brooklyn, MI 49230 P: 800.805.9728 www.theflagpolecompany.com



The Flagpole Professionals!



F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Solid Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers **E** Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **D** Butt Diameter **ESR-GS** Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

Set

and Hardwood Wedges (By Installer)

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate

Lightning Spike -

3/4" Diameter Steel Rod

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Model # EH205125



TRK-9610 In-Line Truck Single Revolving



BAL-0512-GLD HD Gold Anodized Aluminum Ball



CLA-9090-SAT | 6.5' from bottom Cleat Only



FC-11 Spun Alum

1-Piece



SAT Satin Finish

Specifications	
A. Mounting Height: 20'	
B. Set Depth: 2'-0"	
C. Total Length: 22'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .125"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 65 lbs.	
Hardware Weight: 9 lbs.	
Ground Sleeve Weight: 23 lbs.	
* Max Flag Size: 4' x 6'	
* Max Wind Speed w/Nylon Flag: 136 mph	
* Max Wind Speed No Flag: 229 mph	
* Wind Speed Specifications from	

ANSI/NAAMM FP 1001-07



Note: Foundation design not included. Foundation dimensions should be determined by a qualified

Engineer familiar with site

soil conditions.