The Flagpole Company PO Box 765 221 N. Main St. Brooklyn, MI 49230 800.805.9728 www.theflagpolecompany.com

F Top Diameter

Mounting Height

Set

C Total Length



Truck and Ornament (Options Available)

See Specification Box

Halyard, #10 (5/16" Diameter) Braided Polyester Rope

E Wall Thickness

See Specification Box

D Butt Diameter

See Specification Box Perimeter caulked by Installer

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate

Alloy 6063-T6 Tapered Aluminum Tube

Cleat (Security Options Available)

Aluminum Collar (Options Available)

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Two (2) Solid Brass Flagsnaps and Two (2) Neoprene Flagsnap Covers

MODEL# EH205188



TRK-9610 In-Line Truck Single Revolving



BAL-0512-GLD HD Gold Anodized Aluminum Ball



CLA-9090-SAT | 6.5' from bottom



FC-11 Spun Alum 1-Piece



Satin Finish

| - | - | 1000 |
|-------------|--------|------|
| 重音 | - 100 | |
| B 33 | 100 | |
| 图 部 | 190 | |
| 康 福 | 180 | |
| 康 題 | - 100 | |
| 200 | - 100 | |
| E 13 | 201 | |
| 原 篇 | - 1911 | |
| B S | - 2011 | |
| 200 | - 80 | |
| E 53 | - 100 | |
| B 88 | - 1811 | |

| Customer Name: | | |
|----------------|-----------|--|
| Dealer: | Qty: 1 | |
| Project: | Location: | |
| Notes: | | |
| | | |
| | | |
| | | |
| | | |

Lightning Spike -

3/4" Diameter Steel Rod

| Specifications |
|--|
| A. Mounting Height: 20' |
| B. Set Depth: 2'-0" |
| C. Total Length: 22'-0" |
| D. Butt Diameter: 5" |
| E. Wall Thickness: .188" |
| F. Top Diameter: 3" |
| Flagpole Sections: 1 |
| Shaft Weight: 86 lbs. |
| Hardware Weight: 9 lbs. |
| Ground Sleeve Weight: 23 lbs. |
| * Max Flag Size: 4' x 6' |
| * Max Wind Speed w/Nylon Flag: 182 mph |
| * Max Wind Speed No Flag: 287 mph |
| |
| * Wind Speed Specifications from |
| ANSI/NAAMM FP 1001-07 |

ESR-GS

Note: Foundation design not included. Foundation dimensions should be determined by a qualified

Engineer familiar with site

soil conditions.