The Flagpole Company PO Box 765 Brooklyn, MI 49230 800.805.9728 www.theflagpolecompany.com



The Flagpole Professionals!



F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard, #10 (5/16" Diameter) Braided Polyester Rope **Mounting Height** Two (2) Nickel Plated Cast Zinc Flagsnaps and Two (2) Neoprene Flagsnap Covers **E** Wall Thickness C Total Length Alloy 6063-T6 Tapered Aluminum Tube Cleat (Security Options Available) See Specification Box **ESS-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Note: Foundation design Waterproof Compound **B** Depth not included. Foundation (By Installer) dimensions should be **PVC Ground Sleeve** determined by a qualified Engineer familiar with site Set Tamped Dry Sand soil conditions. (By Installer)

Customer Name: Dealer: Qty: 1 Project: Location: Notes:

MODEL # EHR-203125




TRK-9101 External Truck Single Stationary



BAL-0412-GLD HD Gold Anodized Aluminum Ball



CLA-9090-SAT | 6.5' from bottom Cleat Only



COL1-A03S

FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 20'
B. Set Depth: 2'-0"
C. Total Length: 22'-0"
D. Butt Diameter: 3"
E. Wall Thickness: .125"
F. Top Diameter: 2"
Flagpole Sections: 1
Shaft Weight: 40 lbs.
Hardware Weight: 3 lbs.
Ground Sleeve Weight: 4 lbs.
* Max Flag Size: 4' x 6'
* Max Wind Speed w/Nylon Flag: 83 mph
* Max Wind Speed No Flag: 108 mph
* Wind Speed Specifications from
ANSI/NAAMM FP 1001-07

