The Flagpole Company PO Box 765 221 N. Main St. Brooklyn, MI 49230 800.805.9728 www.theflagpolecompany.com



The Flagpole Professionals!



## MODEL # EHR254125



TRK-9301
External Single Stationary
Aluminum Truck With Solid
Aluminum Pulley



BAL-0412-GLD HD Gold Anodized Aluminum Ball



CLA-9090-SAT | 7' from bottom Cleat Only



FC-11 Spun Alum 1-Piece



SAT Satin Finish

7	1		2-0	See Specification Box	
C Total Length	_		-	Halyard, #10 (5/16* Diame Braided Polyester Rope	eter)
	A Mounting Height		370 ◀	Two (2) Nickel Plated Cast and Two (2) Neoprene Flag	
				E Wall Thickness Alloy 6063-T6 Tapered Alu	uminum Tube
	~~	0	(0,0)	Cleat (Security Options of See Specification Box	Available)
			/	<b>D</b> Butt Diameter	ESS-GS
				<b>Aluminum Collar</b> (Options Available) See Specification Box Perimeter caulked by Installer	
	B Set Depth		KK.	2" Cap - Cement or Waterproof Compound (By Installer) - PVC Ground Sleeve	Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site
_	, s,			· Tamped Dry Sand (By Installer)	soil conditions.

F Top Diameter ← Truck and Ornament (Options Available)

NOMINAL EXPOSED HEIGHT: Total Shaft Length of 25' flagpoles is 26'-6" with a Set Depth of 2'-6". With the Truck and Ornament attached, the nominal Mounting Height is 25'.

Tioninal Mounting Fleight is 25.	
Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

