The Flagpole Company PO Box 765 221 N. Main St. Brooklyn, MI 49230 800.805.9728 www.theflagpolecompany.com



The Flagpole Professionals!



F Top Diameter Truck and Ornament (Options Available) See Specification Box Halyard Assembly, #10 (5/16" Diameter) Polyester Rope A Mounting Height Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube C Total Length Flush Access Door with Keyed Lock, Continuous Piano Hinge, and Manually Operated Cam Cleat **D** Butt Diameter **ICC-GS** Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Depth Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Tamped Dry Sand (By Installer) Set Note: Foundation design not included. Foundation 3/16" Steel Plate Welded to Sleeve dimensions should be determined by a qualified 3/16" Steel Support Plate Engineer familiar with site 12 Lightning Spike soil conditions. 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	
1	

MODEL # IC205125



TRK-9660
Int. Revolving Truck
Sealed Bearings



BAL-0512-GLD HD Gold Anodized Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish



ICC - CAM CLEAT Flush Mount Hinged Door

0	
Specifications	
A. Mounting Height: 20'	
B. Set Depth: 2'-0"	
C. Total Length: 22'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .125"	
F. Top Diameter: 3"	
Flagpole Sections: 1	
Shaft Weight: 72 lbs.	
Hardware Weight: 17 lbs.	
Ground Sleeve Weight: 23 lbs.	
* Max Flag Size: 4' x 6'	
* Max Wind Speed w/Nylon Flag: 117 mph	
* Max Wind Speed No Flag: 204 mph	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

