



Model IC-407156

8" - 14 gauge spun aluminum ball
gold anodized.

Single sheave truck, cast aluminum
revolving, non-fouling, internal
halyard truck

One length #6 wire center halyard,
with 2 flag snaps and covers

One 2" x 3-1/2" vinyl covered
counterweight with eyelet

Beaded retaining ring

Access opening with cylinder lock

Aluminum flash collar

3000 PSI concrete

Hardwood wedges
(supplied by others)

Dry sand tightly tamped
after aligning pole

Foundation sleeve -16 ga
hot dip galvanized steel

Steel centering wedges

1/4" Steel base plate

1/4" Steel support plate
welded to grounding spike

Exposed height: 40'-0"

Tapered portion: 22'-9"

Overall length: 44'-0"

Access height: 5'-0"

Straight portion: 21'-3"


Foundation: 4'-6"

4'-0"

6"

12"

18"
48"



Revolving non-fouling internal halyard
truck, cast aluminum body, 26
stainless steel ball bearings,
and 2-1/2" diameter plated
steel sheave.

Cam-action cleat
with sheave

Cylinder lock


Door for access
opening

Access opening

All shafts with overall
length of more than
38'-6" are shipped in
two sections.

2 Sections. Each section
matched marked for field
assembly. Exposed
portion of jam sleeve must
be **well lubricated** prior to
assembly.

1-1/2" maximum shop
gap allowed for field
fitting (ram for tight joint)



Project:	Ground set tapered aluminum flagpole: ALLOY: 6063T6	The Flagpole Company	Date:
Location:	Exposed height: 40'-0"	Overall height: 44'-0"	Revision:
Architect:	Ships in 2 Sections	Butt diameter: 7"	
Contractor:	Top diameter: 3-1/2"	Wall thickness: .156"	
Customer:	Finish: 100 grit polish		