

R80WLED Field Adjustable Flood Lights

TECHNICAL SPECIFICATIONS (CONTINUED)

ELECTRICAL

Drivers:

Constant Current, Class 2, 120-277V, 50/60 Hz
Constant Current, Class 1, 480V, 50/60 Hz

R80WLED @ 5000k/4000k

52W: 120V: 0.44A, 208V: 0.25A, 240V: 0.22A, 277V: 0.19A
80W: 120V: 0.67A, 208V: 0.39A, 240V: 0.34A, 277V: 0.29A

Surge Protection

R80WLED: 6kV

ELECTRICAL

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems.
Requires separate 0-10V DC dimming circuit. Dims down to 10%.

OPTICAL

NEMA Type:

NEMA Beam Spread of 7H x 6V

OTHER

Warranty


Our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. Warranty is subject to all terms and conditions found at www.theflagpolecompany.com

Buy American Act Compliance:

We value USA manufacturing! Upon request, we may be able to manufacture this product to be compliant with the BUY American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

R80WLED 52W/80W

Weight 11 lbs



The Flagpole Company
PO Box 765
221 N. Main St.
Brooklyn, MI 49230
800.805.9728
www.theflagpolecompany.com

R80WLED		4000K	5000K		4000K	5000K
Wattage		52W	52W		80W	80W
Input Watts		57.5W	56.4W		77.0W	75.9W
Lumens		8138	8290		10440	10813
Lm/W		141.5	147.0		135.5	142.4
CRI		82	82		82	82
Voltage Ratings		120-277V			120-277V	

