



## FALCON RIDGE

2515 Bypass Rd. Flemingsburg, KY 41041

606-845-7439

### **Instructions for Installation and Care of RTV 900 Soft Door/Rear Window Combo** KU-RTV900-DRW01

**Notice: Do not smoke inside the cab or expose the enclosure to direct flames. Cab is Flammable.**

- Be sure to read these instructions thoroughly before opening and installing the RTV 900 Soft Door/Rear Window Combo. The installation is best done when the temperature is 60 degrees F. or warmer.
- Carefully open the carton and remove the rolled up Cab Enclosure on a large flat surface that is clean and free of dirt or other material.
- Check over the parts included in the carton with the parts list shown below:

|                     |         |          |
|---------------------|---------|----------|
| Velcro Hook strips: | 6 each  | 8" long  |
| “ “                 | 2 each  | 10" long |
| “ “                 | 2 each  | 14" long |
| “ “                 | 2 each  | 15" long |
| “ “                 | 1 each  | 25" long |
| Snap studs          | 21 each |          |
| Cab Enclosure       | 1 each  |          |



- Before beginning installation you must first remove the hardware holding the top along the rear, this will be all the removal necessary to install the Door/Rear Window Combo. It will also help installation if you first raise the bed.
- First take the time to place a few pieces of adhesive Velcro. The first will be at the top of rear window under the hard top. Lifting up on the rear of the hard top, place the 25" adhesive strip on the top of the roll cage slightly leaning toward the front. Next attach the two 14" adhesive Velcro strips under the plastic piece at the bottom of the rear window. See photo below.



- You will see six 8" adhesive Velcro strips with the cab. These will be attached to the inside of the windshield down the sides. Three pieces per side have been supplied because it is a curved piece of metal and the adhesive Velcro does not curve well. The photo below shows where to attach these.



- Now that these Velcro strips have been installed you can now pass the enclosure behind the cab. Temporarily attach the front of the doors to the window while you attach the top and bottom of the rear window (Being sure to center correctly). Once the rear window is secure, pull the doors forward and attach to the window along the inside edge.
- Now get in the cab and close the door. While someone else lifts up on the rear of the hard top, pull the top of the door up over the roll bars going front to back. Once you see where to attach the remaining Velcro pieces, do so and connect the top of the door here. **NOTE: YOU DO NOT NEED TO PULL UP ON THE DOOR TIGHTLY, LEAVING IT SLIGHTLY LOOSE MAKES IT WORK BETTER.**
- Mark the desired locations for the stud snaps on the fenders and side panels. Then install the stud snaps to the RTV using only a #2 phillips screwdriver. **Caution: Do not use a drill as damage to the RTV's gas tank can occur! See Photo Below:**



- To open and stow the doors, move the zipper fully rearward and fold the bottom portion of the doors up. Then begin to form a vertical roll with the door by rolling it inward from

the front edge toward the rear of the door. Secure in place using the two hook and loop straps provided. Try to form a roll approximately 2” in diameter to assure that the door will not stick out very far while stowed.

#### Cleaning and Storage Recommendations:

- Before removing the Falcon Ridge Cab for storage, make sure it is very clean in order to prevent scratching of the window panels. Clean with a soft rag or sponge using a mild liquid detergent soap and warm water solution. Never rub the windows with a dry cloth or rag! Let the Cab dry thoroughly before attempting to roll for storage.
- It is important that the Cab be rolled up for storage rather than folding. Folding will cause damage to the windows!!! Carefully roll up the Cab similar to the way it was when it was packed at the factory. On a large, clean and flat surface, fold the doors over the rear panel first, then, interleave the top and windshield on top of the doors. Begin rolling the Cab into a roll approximately 8 inches in diameter. Put the rolled Cab back into the carton for storage at a normal room temperature. It is best not to expose the Cab to either extreme hot or cold temperatures when storing.
- A special cleaner conditioner is available from Falcon Ridge that will greatly increase the service life of the Cab Enclosure. In addition, if additional hook and loop sets are needed, they can also be ordered.

## Return Policy

If for any reason you choose to return this product it must be returned within **30 days from date item is received**. You **MUST** package the product exactly **as it was originally packaged from the factory to get a full refund for the product!**

The vinyl windows should never be folded when packaging in the box or for storage purposes. Lay all the windows on top of each other with the canvas folded in between and the paper (if available) on both sides of the windows.

**All returned products will be inspected upon arrival at the production facility and must be in unused, factory new condition to receive refund - a 25% restocking fee will apply.**

If ordered from Falcon Ridge please call at 606-845-7439 to gain a return authorization number, use our preferred shipping carrier (UPS) to return the item (unless the item is defective, you are responsible for paying the shipping to return the item.) **Any returns submitted to Falcon Ridge without a return authorization number will be charged a 20% restocking fee.** If ordered from one of Falcon Ridges many distributors', you must first call them and see what their return policy is. Once your item reaches our production facility, our customer satisfaction team will inspect your item to ensure unused, factory new condition. **NOTE: All windshields must be returned with the original protective film intact and not removed. Do NOT REMOVE if**

**you have any intentions of returning the item. Refund/ replacement of a windshield will only be processed on items with original protective film or if the windshield is defective.**

Items must be properly packaged in the original shipping carton to protect them during transit and ensure your returned item arrives back factory fresh, and in new resalable condition (**any returned items that have been used, altered or damaged in any way will not be subject for a refund.**) All contents including instruction manuals, accessories, hardware, Velcro, etc. must be included in your return shipment. Only items in OEM factory new condition will be approved. Once returned items are received, credit will be issued to the original credit card/ payment method used for the purchase. Outbound shipping and return shipping cost will not be refunded. Please allow 4 to 6 weeks for your refund to be processed.

## **Warranty**

To The Owner of this Product:

Thank you for purchasing one of Falcon Ridge Cab Enclosures, Tops &/or Windshields! Below are the terms under which your product is covered under our manufacturer's warranty.

30 Day Warranty which includes and is not limited to replacing the enclosure, tops and/or windshield due to defect of the product. Please refer to the return policy in this case for more information.

1 Year Warranty includes any defect in material or workmanship within this time frame we will gladly correct the problem or replace the enclosure, tops &/or windshield. Upon submitting for the correction or replacement we will need to receive pictures of the defect in material or workmanship along with the receipt from the date of purchase.

Thank you,

Falcon Ridge