



WALK ALL OVER



WALK THE WALK



WALK RIGHT UP

WALK ALL OVER, WALK THE WALK AND WALK RIGHT UP

Protect your floors and the first impression of your business. Our entryway products were developed to trap dirt and moisture, protecting against unwanted debris that would otherwise be tracked into your facility.

WALK ALL OVER

WALK THE WALK

WALK RIGHT UP

Product Type	Carpet Tile	Carpet Tile	Carpet Tile
Construction	Tufted	Tufted	Tufted
Gauge	5/32" (25.2 rows per 10 cm)	5/32" (25.2 rows per 10 cm)	5/32" (25.2 rows per 10 cm)
Tufted Weight	30 oz/yd ² (1017 g/m ²)	38 oz/yd ² (1288 g/m ²)	38 oz/yd ² (1288 g/m ²)
Pile Thickness	.145" (3.68 mm)	.203" (5.16 mm)	.144" (3.66 mm)
Stitches Per Inch	10.0 (39.37 per 10 cm)	8.5 (33.43 per 10 cm)	8.5 (33.43 per 10 cm)
Density	7,448	6,739	9,500
Dye Method	100% Solution Dyed	100% Solution Dyed	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon	Colorstrand® SD Nylon	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic	Non-Woven Synthetic	Non-Woven Synthetic
Secondary Backing	UltraSet®	UltraSet®	UltraSet®
NSF 140	Gold	Gold	Gold
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight	Contains a minimum of 39% pre-consumer recycled content by total product weight	Contains a minimum of 39% pre-consumer recycled content by total product weight
Indoor Air Quality	Green Label Plus Certified # 1098	Green Label Plus Certified # 1098	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)	24" x 24" (.6096 m x .6096 m)	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Vertical Ashlar	Quarter Turn / Monolithic / Brick Ashlar / Vertical Ashlar / Multi Directional	Quarter Turn / Monolithic / Brick Ashlar / Vertical Ashlar / Multi Directional
Flammability	ASTM E 648 Class 1 (Glue down)	ASTM E 648 Class 1 (Glue down)	ASTM E 648 Class 1 (Glue down)
Smoke Density	ASTM E 662 Less than 450	ASTM E 662 Less than 450	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV	AATCC-134 Under 3.5 KV	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Severe Traffic	Severe Traffic	Severe Traffic
Warranties	Lifetime Limited Wear Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Lifetime Limited Colorfastness to Light 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Atmospheric Contaminants	Lifetime Limited Wear Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Lifetime Limited Colorfastness to Light 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Atmospheric Contaminants	Lifetime Limited Wear Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Lifetime Limited Colorfastness to Light 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Atmospheric Contaminants

Cover: Walk All Over Carpet Tile 955 - Cobalt, Walk the Walk Carpet Tile 955 - Cobalt and Walk Right Up Carpet Tile 955 - Cobalt



859
Walk the Walk



955
Walk the Walk



983
Walk the Walk



989
Walk the Walk



Up to 2,000 sq. yds. available within 10 business days or less

