

## unveil

collection	<b>vertical layers</b>	
style number	<b>0601V</b>	
construction	<b>commercial luxury vinyl tile</b>	
class / ASTM F1700	<b>class III, type B</b>	
finish	<b>ExoGuard™</b>	
	u.s.	metric
nominal dimensions	<b>9 in w x 36 in l</b>	<b>23 cm w x 91.5 cm l</b>
actual dimensions	<b>9 in w x 36 in l</b>	<b>22.86 cm w x 91.44 cm l</b>
wear layer thickness	<b>30 mil (0.03 in)</b>	<b>0.76 mm</b>
overall thickness	<b>0.118 in</b>	<b>3 mm</b>
edge profile	<b>square</b>	
installation	<b>direct glue</b>	
recommended adhesive	<b>shaw 4100, s150 or shaw 4151</b>	

### packaging


pieces per box	<b>16 pcs</b>	
area per box	<b>36 sq ft</b>	<b>3.34 sq m</b>
weight per box	<b>35.27 lbs</b>	<b>16 kg</b>




### recommended installation method



**ashlar**



**brick**



**herringbone**



**stagger**

### performance + testing

static load (ASTM F970)	<b>passes (modified), *2000 PSI</b>
residual indentation (ASTM F1914)	<b>passes</b>
resistance to heat (ASTM F1514)	<b>passes</b>
resistance to light (ASTM F1515)	<b>passes</b>
resistance to chemicals (ASTM F925)	<b>passes</b>
smoke density (ASTM E662, flaming mode)	<b>passes</b>
radiant panel (ASTM E648)	<b>passes, class I</b>

\*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.

## warranties

[15 year commercial limited](#)

[commercial limited underbed bond](#)

## product transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. Luxury Vinyl Tile products are UL Certified with an Industry-Wide EPD and are assessed for impacts on human health and the environment.

## attributes + certifications

Environmental Product Declaration (EPD)

**[3rd party certified in accordance with ISO 14025, EN 15804, and ISO 21930:2017](#)**

FloorScore®

**[Certified](#)**

CE marking (EN 14041)

**3rd party certified**

## green leed contribution credit

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration

**RFCi Industry Average EPD (50%)**

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

**Floorscore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

