HARDWOOD

CORNERSTONE OAK

Engineered







CORNERSTONE OAK

HARDWOOD

	US Units	Metric Units
Style Number	SW676	
Construction	Engineered	
Species	White Oak	
Nominal Overall Thickness	3/8"	9.5 mm
Nominal Width	5"	127 mm
Finish	UV Aluminum Oxide	
Gloss Level	7%	
Surface Texture	Wirebrushed	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	36.61 lbs	16.6 kg
SQFT per Carton	29.53 sq ft	2.74 sq m
SQFT per Pallet	1181.2 sq ft	109.73 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
All measurements are nominal.	Cartons may include random lengths.	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)

















Flush Reducer

*Overlap Reducer

SSH38 Flush Stairnose

SOSH8

*Overlap Stairnose Threshold / Carpet Reducer

TMH78 T-Molding

Quarter Round

shawfloors.com