

HARDWOOD

FIFTH AVENUE OAK engineered



1007 Astor



1028 Carnegie



7024 Morgan



9016 Cabot



5014 Roosevelt

FIFTH AVENUE OAK

HARDWOOD

Style Number	SW663
Construction	Engineered
Thickness	1/2" (12mm)
Width	4.72"
Species	White Oak
Texture	Wire Brushed
Gloss Level	7%
Janka Hardness Rating	1360
Edge Description	Microbeveled
End Description	Microbeveled
SF per carton	27.90
SF per pallet	892.80
Installation	Glue Down
All measurements are nominal	

Features

- Contemporary urban color palette with matte finish and wire brushed texture
- Engineered for pattern installations such as herringbone, basketweave, brick, etc.
- Left and Right planks packaged together for easy ordering
- Each plank measures 4.72" x 23.62" (120mm x 600mm), 5:1 ratio width:length

Sundry Recommendations

Style #	Style Name	Coverage	Moisture	Additional Features
ADHESIVES				
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
111SA	3-in-1 Ultra — MS	35 SF / gal for moisture	No moisture test required	Sound control & crack suppressant
		70 SF / gal as adhesive	Up to 5 obs. or 85% RH	
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required	
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH	
		60 SF / gal	Up to 5 lbs. or 85% RH	

Trim Pieces length: 78"

				
SRH12 Flush Reducer	SSH12 Flush Stairnose	SCH12 Threshold Carpet Reducer	TMH78 T-Molding	QTR96 Quarter Round

Benefits

